

SoliTherm TOP & 19" rack mounted

Part-no.	Cooling capacity L35L35 / L35L50 (DIN3168)	Voltage / Frequency	Operating temp. range	IP protection to IEC 60 529 Ext/ Int	Weight (Kg)	QR Code
----------	---	---------------------	--------------------------	---	-------------	---------

Dimensions (H x W x D): 230 x 430 x 330 mm

44820001	450 W / 280 W	230 V - 50/60 Hz	+20°C - +50°C	24 / 54	23	Click here for full technical specifications KG 4482
44821001	450 W / 280 W	120 V - 60 Hz	+20°C - +50°C	24 / 54	23	

Dimensions (H x W x D): 400 x 600 x 400 mm

45550001	1.1 kW / 700 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	55	Click here for full technical specifications KG 4555
45551001	1.1 kW / 700 W	120 V - 60 Hz	+20°C - +55°C	24 / 54	55	
45552001	1.1 kW / 700 W	400/460 V - 50/60 Hz 3~	+20°C - +55°C	24 / 54	55	

19" Rack mounted

45330001	550 W / 370 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	28	Click here for full technical specifications KG 4533
45340001	850 W / 590 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 54	33	Click here for full technical specifications KG 4534
4535000	900 W / 700 W	230 V - 50/60 Hz	+20°C - +55°C	24 / 44	45	Click here for full technical specifications KG 4535
4535100	900 W / 700 W	120 V - 60 Hz	+20°C - +55°C	24 / 44	45	