

## Outdoor Air Conditioner KG 8520-230V



### Product Features

|                           |                                                 |
|---------------------------|-------------------------------------------------|
| <b>Brand Name:</b>        | SlimLine Pro                                    |
| <b>Order Number:</b>      | 852000001                                       |
| <b>Color:</b>             | RAL 7035                                        |
| <b>Housing Material:</b>  | Mild steel, powder coated                       |
| <b>IP class EN 60529:</b> | IP 56                                           |
| <b>Optional:</b>          | With 1,000 W cabinet heater order no. 852001001 |
| <b>Approvals:</b>         | CE, RoHS, cURus (Q4/18)                         |
| <b>Taric Code:</b>        | 84158200                                        |

## Technical data KG 8520-230V

|                                 |                                                                |
|---------------------------------|----------------------------------------------------------------|
| <b>Cooling capacity L35L35:</b> | 2 kW                                                           |
| <b>Cooling capacity L35L50:</b> | 1,5 kW                                                         |
| <b>Heating capacity:</b>        | 1,000 W (optional)                                             |
| <b>Compressor:</b>              | Reciprocating compressor                                       |
| <b>Refrigerant / GWP:</b>       | R134a / 1430                                                   |
| <b>Temperature range:</b>       | -40°C - +60°C                                                  |
| <b>Air volume flow:</b>         | Ambient air circuit: 750 m³/h<br>Cabinet air circuit: 450 m³/h |
| <b>Mounting:</b>                | External / recessed                                            |
| <b>Dimension HxWxD:</b>         | 1,350 x 395 x 210 mm                                           |
| <b>Weight:</b>                  | 52 kg                                                          |
| <b>Voltage / Frequency:</b>     | 230 V ~ 50/60 Hz                                               |
| <b>Current L35L35:</b>          | 4.7 A                                                          |
| <b>Starting current:</b>        | 16 A                                                           |
| <b>Max. current:</b>            | 6.5 A                                                          |
| <b>Nominal power L35L35:</b>    | 1,050 W                                                        |
| <b>Max. power:</b>              | 1,500 W                                                        |
| <b>Fuse:</b>                    | 12 A (T)                                                       |
| <b>Connection:</b>              | Connection terminal block                                      |

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview product group Cabinet cooling units - SlimLine Pro](#)

